





Removing graffiti has never been easier. Safely remove unwanted graffiti, marker, and other "tags" from concrete and block surfaces, lockers, road signs, rail cars, and anywhere else graffiti is found. Maintain original appearances without the need for repainting.

680HS Hard Surface Graffiti Remover

For use on: metal, such as lockers, bathroom stall walls, rail cars, and road signs, plastics, playground equipment, and glass

Do Not Use On: PVC, drywall, limestone, terrazzo tile, rubber, plexiglass or other clear acrylic sheets

Application: Spray on surface to be cleaned and gently scrub with a paper towel, cloth, or scrub pad. Graffiti should immediately begin to lift from surface. If ghosting remains, repeat process.

Clean Up: Use **BLUE BEAR 700DG Degreaser** or water and a cloth, scrub brush, or mop, to clean remaining residue.

Biodegradable: Meets or exceeds ASTM standards

Precautions: Concrete surfaces may darken with use of **680HS**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

Warnings: May cause skin irritation. May cause eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. This product contains a chemical known to the state of California to cause cancer. Keep out of reach of children.

Flash Point: Above 200°F (93.3°C)

pH Level: Neutral

VOC (Volatile Organic Compounds): 1.5%, 0.1 lb/g, 14.4 g/l

California and OTC Compliant

Ingredients: Benzyl Alcohol, Dibasic Ester LVP, Soy Ester, Proprietary Surfactant Blend

682PS Porous Surface Graffiti Remover

For use on: unfinished/uncoated concrete, stone, landscaping block, bare brick

Do Not Use On: PVC, drywall, liimestone, terrazzo tile, rubber, plexiglass or other clear acrylic sheets

Application: Spray on surface to be cleaned and allow to sit for a few minutes. Use either a stiff, natural bristled brush, or metal brush to agitate. Wait until paint starts to buckle or lift before power washing. Heavier coatings may require reapplication of product before power washing. Repeat entire process if necessary.

Clean Up: Use **BLUE BEAR 700DG Degreaser** or water and a scrub brush or power washer to clean remaining thin residue.

Biodegradable: Meets or exceeds ASTM standards

Precautions: Concrete surfaces may darken with use of **682PS**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

Warnings: Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May be harmful if swallowed. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm and cancer. Keep out of reach of children.

Flash Point: Above 200°F (93.3°C)

pH Level: 8.1 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds): 29.1%, 290.8 lb/g, 2.4 g/l California and OTC Compliant

Ingredients: N-Methyl Pyrrolidone, Benzyl Alcohol, Dibasic Ester, Soy Ester, Proprietary Surfactant Blend

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night USA and Canada: **800.242.9300**CCN717946 or **+1 703.527.3887** (Collect Calls Accepted)

NON-EMERGENCY:

Call: 800.538.5069 Or visit www.franmar.com

