



280AH

AUTOMOTIVE ADHESIVE REMOVER

EASY REMOVAL OF DOUBLE-SIDED TAPE

- Removal is Simple, Easy, and Safe
- Made with 100% American Grown Soybeans
- Eliminates Sanding and Grinding
- Actual job-man hours are reduced by over 75%
- 280AH will continue to work effectively for up to three months



Find Out More About 280AH Automotive Adhesive Remover

Visit: www.franmar.com or
Call: 800.538.5069





PRODUCT DATA



280AH Automotive Adhesive Remover (Formerly BEAN•e•doo® Auto Adhesive Remover)

BLUE BEAR® 280AH is an innovative and effective product for body shops and classic car enthusiasts. Specially formulated **280AH** eliminates damage to moldings caused by sanding, grinding, or using “the wheel” and saves at least 50% of man hours compared to using mechanical removal methods.

Application:

Soak automotive molding for a few hours but no longer than overnight. Once adhesive has softened, scrape off with a plastic scraper.

Clean Up:

After adhesive has been removed, rinse thoroughly with water to remove remaining residue.

Usage Tip from the Pros:

- Keep dip tray lid closed or covered when not in use.
- Do not use on chrome mylar moldings.

Biodegradable:

Meets or exceeds ASTM standards

Precautions:

Prolonged periods of soaking may soften or remove paint. **280AH** solution will remove chrome mylar tape found on body side moldings. Will cause rubber moldings to swell. Do not use with very thin moldings.

Warnings:

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May be harmful if swallowed. Keep out of reach of children.

Flash Point:

149°F (65°C)

pH Level:

5.4 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

29.46%, 2.22 lb/g, 265.69 g/l, California and OTC Compliant

Ingredients:

Soy Ester, D-Limonene, Proprietary Surfactant Blend, Tripropylene Glycol

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702

Rev. 3/6/2015