



PRODUCT DATA

540PM Polyurethane Adhesive Remover (Formerly Poly-U Adhesive Remover)

BLUE BEAR® 540PM is specifically formulated to remove polyurethane-based adhesive. It cleans up polyurethane adhesive that seeps through floor slats and even adhesive that gets tracked across the floor by workers' shoes. The easy-to-use gel formula allows application to only affected areas.

Coverage:

Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

Horizontal: Average coverage is 125 sq ft per gallon (max 200 sq. ft. per gal.)

Vertical: Average coverage is 75 sq ft per gallon

Application:

For large application areas, test in a small, inconspicuous area before using on complete project.

For Pre-Engineered Flooring Surfaces:

Pour or spread a small amount of **540PM** on the adhesive. Let **540PM** dwell for a couple of minutes if adhesive has just come in contact with floor. Let it dwell for 15-60 minutes for adhesives that have been in place longer. Once adhesive is softened, wipe up or scrape **540PM** and adhesive from the floor. Wipe surface with wet cloth to remove remaining residue.

For Wood Floors on Concrete Surfaces:

Pour or spread **540PM** 1/8" thick over highest level of adhesive. Let dwell for 8-12 hours. Scrape **540PM** and adhesive off concrete. Rinse residue off with water.

Usage Tips from the Pros:

- Block off areas of application from foot traffic, to prevent slips and unwanted tracking of product.
- Do not leave product on pre-engineered flooring any longer than necessary.
- For best results, use above 50°F (10°C).

Biodegradable:

Meets or exceeds ASTM standards

Precautions:

Do not use on site-applied coatings or sealers.

Warnings:

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. May be harmful if swallowed. Keep out of reach of children.

Flash Point:

Above 200°F (93.3°C)

pH Level:

8.1 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

49%, 4.249 lb/g, 509 g/l, California and OTC Compliant

Ingredients:

N-Methyl Pyrrolidone, Dibasic Ester LVP, Soy Ester, Proprietary Thickening and Surfactant Blend

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702

Rev. 3/6/2015