



PRODUCT DATA

620LQ Liquid Coatings Remover (Formerly SOY•Gel™ Liquid)

BLUE BEAR® 620LQ is formulated to safely dip metal, glass, and other non-plastic, non-wood materials in a dip application. Safe, low odor, non-caustic, and green, **620LQ** effectively removes multiple layers of a variety of coatings, including lead based paint*.

**Ideal for lead-based paint removal. The lead becomes encapsulated in the gel, preventing airborne particles and allowing for safe removal. Dispose of in accordance with all existing local, state, and federal ordinances.*

Application:

Do not use on wood.

Dip metal parts in **620LQ**. Check the progress of the stripping action by using a scraper to see if the coating is softened down to the surface. If not, wait longer and recheck. Once the coating is softened, remove it with a scraper or other stripping tool.

Clean Up:

Using a cloth or fibrous scrub pad, clean remaining residue with **BLUE BEAR 700DG Degreaser** or water. Allow surface to dry before further preparations.

Usage Tip from the Pros:

Usage Tips from the Pros:

- Keep dipping tray/bin covered when not in use, to keep debris and other items from falling in.
- Abrading tough coatings before dipping helps accelerate removal.
- Most parts can safely be left in overnight.

Biodegradable:

Meets or exceeds ASTM standards

Precautions:

Always use care to prevent **620LQ** from getting on surfaces not intended to be stripped. **Do not dip wood products.** **620LQ** will cause glued joints to separate.

Warnings:

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. Keep out of reach of children.

Flash Point: Above 200°F (93.3°C)

pH Level: 8.1 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

49%, 4.249 lb/g, 509 g/l, California and OTC Compliant

Ingredients:

N-Methyl Pyrrolidone, Dibasic Ester LVP, Soy Ester, Proprietary Thickening and Surfactant Blend

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night

USA and Canada: **800.242.9300**

CCN717946 or **+1 703.527.3887**

(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702

Rev. 3/29/2016