



PRODUCT DATA

640TA Low Maintenance VCT/PVCT Tile Sealer Remover (Formerly TOP•Aid™)

BLUE BEAR® 640TA's special blend of finishing remover technology and super-infused surfactants give it fast-acting, superior wetting tension that reduces time and labor needed for lifting low-maintenance floor finishes.

Coverage:

Coverage per square foot varies depending on type and age of coating, number of layers and method of application. Average coverage is 160 sq ft per gallon.

Application:

Due to variances in surfaces and conditions, test in a small, inconspicuous area before using on complete project.

Floor should be cleaned of loose dirt and dust. Liberally pour or mop **640TA** onto floor, ensuring entire floor is covered. Dwell time may be 15-45 minutes. Once penetration has occurred, agitate with black stripping pad.

Clean Up:

Pick up removed coating with a commercial wet/dry vacuum or squeegee sealer into pile and pick up with a wet/dry vacuum. Rinse floor with clean water. Repeat rinse if necessary.

Biodegradable:

Meets or exceeds ASTM standards

Precautions:

If left on too long **640TA** may damage VCT/PVCT tiles. Test a small area before doing full project.

Warnings:

May cause eye irritation. May cause skin irritation on repeated or prolonged contact. May be harmful if swallowed. Excessive inhalation of vapors may cause irritation to the upper respiratory tract.

Flash Point:

>210°F (98.8°C)

pH Level:

8.3 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

40.32%, 3.28 lb/g, 392.8 g/l

Ingredients:

Water, EB Glycol Ether, Benzyl Alcohol, Proprietary Surfactant Blend

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702

Rev. 11/2/2015