



# Concrete Form Release 800GP

## GENERAL PURPOSE FORM RELEASE

- Works with wood, metal, styrene, urethane & fiberglass forms
- 20:1 dilution ratio with water
- Excellent wettability properties
- Achieve fine detail with little to no dusting
- Non-staining and 100% biodegradable



Coverage: Up to 2,500 square feet per gallon

See our full line of products

Visit: [www.franmar.com](http://www.franmar.com) or

Call: 800.538.5069





# PRODUCT DATA



## Concrete Form Release 800GP

**BLUE BEAR® Concrete Form Release 800GP** was developed for general construction with an emphasis on wood forms. **Concrete Form Release** is very forgiving while producing excellent results, and can achieve fine detail with little to no dusting. This high-yield concentrated formula is non-staining, leaves a paintable surface and contains no petroleum, making it environmentally friendly.

**Coverage:** Average coverage is 2,500 square feet per gallon

**Seasoning Forms:** When using **Concrete Form Release** for the first time, season form by applying generous coating and allow to dry. Then spray again for use.

**Surface Preparation:** When using on form that had other release or oil previously applied, scrape particulates and clean form to a usable condition. Spray a generous coating and allow to dry. Spray again for use.

**Mixing:** Add 1 part **Concrete Form Release** to 20 parts clean water. Shake or mix the solution until consistent throughout. Once diluted, if left undisturbed for 1 week, solution may begin to separate. Shake or mix again until consistent throughout.

**Application:** **Concrete Form Release** can be applied by all conventional methods. Spray application is recommended. Remove puddles and allow to dry thoroughly. Proper application will result in fine detail with little to no dusting.

**Do not use or apply in a steady rain. Do not apply to forms still wet from rain or water used in cleanup. Use above 32°F (0°C).**

**Clean Up:** Any spills or overspray can be cleaned with water.

**Storage:** Keep container closed when not in use.

**Precautions:** Dispose of waste according to local regulations. Avoid eye contact. Gloves are recommended for sensitive skin.

**Biodegradable:** Meets or exceeds ASTM standards

**Flash Point:** Above 200°F (93.33°C)

**pH Level:** 5.8 pH of 1/10 wt/wt solution in soft water

**CAUTION:** Causes mild skin irritation. Causes eye irritation. May be harmful if swallowed. Keep out of reach of children.

**Ingredients:** Soy ester, ethoxylated alcohol, TPM proprietary additives

**VOC (Volatile Organic Compound) content:** 5.2%, 0.4 lb/g, 47.9 g/l California and OTC compliant

[www.franmar.com](http://www.franmar.com)  
800-538-5069  
10282 E 1400 North RD  
Bloomington, IL  
61705

**CHEMICAL EMERGENCY:**  
Spill, leak, fire, exposure or accident,  
call CHEMTREC day or night.  
USA and Canada: 800.424.9300  
CCN717946 or +1 703.527.3887



[www.franmar.com](http://www.franmar.com)  
Rev. 7/18/25