

# KEEP YOUR EQUIPMENT FREE OF ASPHALT BUILD-UP

## REMOVE ASPHALT QUICKLY & SAFELY



- Effectively breaks down build-ups of asphalt, polymers, top coatings, sealers and more
- Pre-apply as a surface protectant
- Easier clean up than traditional petroleum-based cleaners
- Made with 100% American-grown soybeans

## EASY TO USE & EASY CLEAN UP

- Spray directly onto asphalt build-up
- Let sit until build-up has softened
- Scrape off build-up with a scraper, or use paper towel/cloth to remove
- Spray surface clean with pressured hose or power washer

*Average Coverage: 100 to 200 square feet per gallon*



**See our full line of products**

Visit: [www.franmar.com](http://www.franmar.com) or

Call: 800.538.5069





# PRODUCT DATA



## BEAN•e•doo® Asphalt Remover

**BLUE BEAR® BEAN•e•doo® Asphalt Remover** is the go-to product for removing asphalt and tar from cars and tools. Our formula breaks down build-ups of asphalt, polymers, top coating, coat tar, dressing, sealers and tac-coatings. Made from 100% American-grown soybeans, **BEAN•e•doo** is simple to use and is biodegradable, making it safe for the environment.

### Usage Tips:

- Pre-apply **BEAN•e•doo** to clean metal surfaces to help prevent asphalt from bonding
- For large jobs or application areas, use a pump-up sprayer with chemical resistant seals
- Build-ups of more than ½" thick may require multiple applications

**Coverage:** Average coverage is 100 to 200 square feet per gallon.

**Application:** (1) Spray undiluted **BEAN•e•doo** directly on asphalt build-up. (2) Let sit until build-up has softened. Thicker build-ups may require multiple applications or longer dwell times.

**Clean up:** Spray clean with pressured hose or power washer.

**Disposal:** Guidelines for waste disposal vary by state. Dispose of in accordance with federal, state and local regulations.

**Storage:** Keep container closed when not in use.

**Precautions:** Not for use on cars manufactured before the mid-90s, or without modern clear coat. Do not use to remove asphalt from concrete surfaces, as more staining may occur. Protect surfaces not intended for **BEAN•e•doo**.

**Biodegradable:** Meets or exceeds ASTM standards

**Flash Point:** Above 425°F (218.33°C)

**pH Level:** 6.65 pH of 1/10 wt/wt solution in soft water

**CAUTION:** This product may cause eye irritation if it enters the eye and may be harmful if swallowed. Use gloves to avoid mild skin irritation and/or dryness. Keep out of reach of children.

**Ingredients:** Soy methyl ester, ethoxylated alcohol

**VOC (Volatile Organic Compound) content:**  
2.3%, .06 lb/g, 20 g/l, California and OTC compliant

www.franmar.com  
800-538-5069  
10282 E 1400 North RD  
Bloomington, IL 61705

**CHEMICAL EMERGENCY:**  
Spill, leak, fire, exposure or accident,  
call CHEMTREC day or night.  
USA and Canada: 800.424.9300  
CCN717946 or +1 703.527.3887



www.franmar.com  
Rev. 7/18/25