

# REMOVES MULTIPLE LAYERS IN JUST ONE APPLICATION



## AWARD-WINNING PAINT STRIPPER

- Removes paints, urethanes, enamels, sealers, some epoxies, lead paint and many other coatings
- Gel formula for easy application
- No methylene chloride or harmful fumes
- Non-caustic and biodegradable
- Made with 100% American-grown soybeans

## EASILY REMOVE MULTIPLE LAYERS

- Apply a thick layer by brushing, pouring, or with a commercial sprayer.
- Use a scraper to check if the coating is softened down to the surface and remove when it is completely softened.

*Horizontal Coverage: 125 square feet per gallon  
Vertical Coverage: 75 square feet per gallon*



**See our full line of products**

Visit: [www.franmar.com](http://www.franmar.com) or  
Call: 800.538.5069



# PRODUCT DATA



## Soy Gel™ Paint & Urethane Stripper

**BLUE BEAR® Soy Gel™ Paint & Urethane Stripper** removes multiple layers and varieties of paint, varnish, urethane, enamels, sealers and some epoxies in one application. Our gel formula clings to vertical surfaces and stays wet for over 24 hours, perfect for any DIY project inside or outside the home. It is safer than many old-fashioned petroleum-based products that are used to remove paint (mineral spirits, ethylbenzene, methanol, xylene, acetone, etc.); is nonflammable, and less VOC's, so less fumes. Works more effectively than other newer, "safe," alternatives in removing many types of paints/coatings. Unlike petroleum-based products, it doesn't allow softened, bubbled-up paint/coatings to re-adhere after only minutes. **Soy Gel** softens paint in 15 minutes to 2 hours or more, depending on the age, type, and number of coatings present.

### Usage Tips:

- For large application areas, use a professional airless sprayer or 4-stage HVLP sprayer.
- For tough coatings or numerous layers, use a notched 1/2" squeegee or 1/4" gauge rake. Square footage will be greatly reduced.
- When used outdoors, cover with a 2 mil or thicker plastic to help keep **Soy Gel** wet and working.

**Test Area:** Due to variances in surfaces and conditions, test **Soy Gel** on a small, inconspicuous area before beginning the full project.

**Application: (1)** Use a paint brush to apply a thick layer of **Soy Gel** over the treatment area. Thickness of the stripper should exceed the thickness of the coatings to be removed. Key to success is to apply thick enough. **(2)** Allow the product to work until the layers of the paint or coating are soft. **(3)** Remove the coatings with a scraper or wet vacuum. Repeat this process as necessary.

**Clean Up:** To remove remaining surface residue, use **BLUE BEAR® Emerge™ Cleaner & Degreaser** or soap and water to thoroughly clean the surface. Allow the surface to fully dry before refinishing.

**Disposal:** Guidelines for paint waste disposal vary by state. Dispose of in accordance with federal, state and local regulations.

**Storage:** Keep container closed when not in use.

**Safe for use on:** Concrete, masonry, wood, metal

**Do not use on:** PVC, drywall, limestone, plastic, veneer, terrazzo tile or rubber

www.franmar.com  
800-538-5069  
10282 E 1400 North RD  
Bloomington, IL 61705

### CHEMICAL EMERGENCY:

Spill, leak, fire, exposure or accident,  
call CHEMTREC day or night.

USA and Canada: 800.424.9300  
CCN717946 or +1 703.527.3887

**Coverage:** Coverage per square foot varies depending on type and age of coating, number of layers and method of application. One gallon will cover approximately 125 square feet on a horizontal surface, and approximately 75 square feet on a vertical surface.

**Precautions:** Concrete surfaces may darken with use of **Soy Gel**. Use a plastic drop cloth to protect floors and surrounding areas, and/or landscaping if outdoors. Open windows to maintain ventilation of the work area. Always wear safety glasses to protect from splatters causing eye irritation, chemical-resistant gloves to protect from skin irritation and dryness, and work-appropriate shoes.

**Biodegradable:** Meets or exceeds ASTM standards

**Flash Point:** Above 200°F (93.3°C)

**pH Level:** 8.1 pH of 1/10 wt/wt solution in soft water

**DANGER:** Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. May cause reproductive harm. Keep out of reach of children.

**⚠ WARNING:** This product can expose you to the chemical n-methyl-2-pyrrolidone, which is known to the state of California to cause birth defects or reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**Ingredients:** N-methyl-2-pyrrolidone, dibasic ester - LVP, soy methyl ester, cellulose ester powder, surfactant, fumed silica

**VOC (Volatile Organic Compound) content:** 49%, 4.249 lb/g, 509 g/l