



Soy Gel Spray™ 610SP Sprayable Coatings Remover

SPECIALLY FORMULATED

- Removes paints, urethanes, enamels, sealers, some epoxies, lead-based paint and more
- Specially formulated for HVLP and commercial sprayers
- Low-odor formula made with 100% American-grown soybeans
- Non-caustic and biodegradable



Horizontal Coverage: 125 sq ft per gallon
Vertical Coverage: 75 sq ft per gallon

See our full line of products

Visit: www.franmar.com or
Call: 800.538.5069





PRODUCT DATA



Soy Gel™ Spray 610SP Sprayable Coatings Remover

BLUE BEAR® Soy Gel™ Spray 610SP Sprayable Coatings Remover is easily applied to vertical or horizontal surfaces and effectively removes multiple layers of topical sealers, acrylics, enamels, urethanes, latex and lead-based paint. **Soy Gel Spray** is a low-odor, non-caustic and green coatings remover.

Usage Tips:

- Mask off areas you do not wish **Soy Gel Spray** to get on
- For veneer finishes, exposure should be in short intervals of

5 to 10 minutes

Coverage: Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

Horizontal: Average coverage is 125 square feet per gallon (maximum 200 square feet per gallon).

Vertical: Average coverage is 75 square feet per gallon.

Test Area: Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

Application: Apply **Soy Gel Spray** thickly with a 3 or 4 stage HVLP (High Volume Low Pressure) sprayer with a 2.5 tip/needle, or an industrial airless sprayer with a .519 tip or larger and a pressure setting of 3000 PSI or higher. Applying too thinly will cause **Soy Gel Spray** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

Clean Up: Use **BLUE BEAR® Emerge™ 700DG Degreaser** or soap and water and a scrub brush, mop or power washer to clean remaining thin residue. Remove excess coating(s) and **Soy Gel Spray** before using a power washer for final cleaning. Allow surface to dry before further preparations.

Storage: Keep container closed when not in use.

www.franmar.com
800-538-5069
10282 E 1400 North RD
Bloomington, IL
61705

CHEMICAL EMERGENCY:

Spill, leak, fire, exposure or accident,
call CHEMTREC day or night.
USA and Canada: 800.424.9300
CCN717946 or +1 703.527.3887

Precautions: Concrete surfaces may darken with use of **Soy Gel Spray**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned. In case of contact with eyes, flush thoroughly with water. Use in a well-ventilated area to avoid respiratory irritation, drowsiness or dizziness. Avoid prolonged contact with skin. Wear safety glasses to avoid splatters causing eye irritation, and chemical-resistant gloves to protect from skin irritation and dryness, etc. Wear work-appropriate shoes.

Biodegradable: Meets or exceeds ASTM standards

Flash Point: Above 200°F (93.3°C)

pH Level: 8.1 pH of 1/10 wt/wt solution in soft water

DANGER: Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation or may cause drowsiness or dizziness. May be harmful if swallowed. May cause reproductive harm. Keep out of reach of children.

⚠️ WARNING: This product can expose you to chemicals including n-methyl-2-pyrrolidone, which is known to the state of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Ingredients: N-methyl-2-pyrrolidone, dibasic ester - LVP, soy ester, ethoxylated alcohol

VOC (Volatile Organic Compound) content:

49.5%, 4.84 lb/g, 578.96 g/l

Safe for Use On: Concrete, masonry, wood, and metal

Do Not Use On: PVC, drywall, limestone, plastic, veneer, terrazzo tile or rubber



www.franmar.com

Rev. 7/16/25