



Poly•U™

540PM

Polyurethane Adhesive Remover

For pre-engineered and concrete floors

SPECIALLY FORMULATED

- Easy-to-use gel formula
- Low-odor
- Cleans up easily with water

5 Gallons 640 FL OZ (18.9L)

DANGER: Eye and skin irritant. See back panel for additional precautionary statements. Keep out of reach of children, V2.0



Poly•U®

540PM

Polyurethane Adhesive Remover

LOW-ODOR & EASY-TO-USE

- For use on pre-engineered and UV-finished wood floors
- Easy-to-use gel formula
- Cleans up easily with water
- Made with 100% American-grown soybeans



Horizontal Coverage: 125 sq ft per gallon

Vertical Coverage: 75 sq ft per gallon

See our full line of products

Visit: www.franmar.com or

Call: 800.538.5069





PRODUCT DATA



Poly•U[®] 540PM Polyurethane Adhesive Remover

BLUE BEAR[®] Poly•U[®] 540PM Polyurethane Adhesive Remover is specifically formulated to remove polyurethane-based adhesive. It cleans up polyurethane adhesive that seeps through floor slats and even adhesive that gets tracked across floors by workers' shoes. The easy-to-use gel formula allows application only to affected areas.

Usage Tips:

- Block off areas of application from foot traffic, to prevent slips and unwanted tracking of product.
- Do not leave product on pre-engineered flooring any longer than necessary.
- For best results, use above 50°F (10°C).

Application:

For large application areas, test in a small, inconspicuous area before using on complete project.

For Pre-Engineered Flooring Surfaces:

Pour or spread a small amount of **Poly•U** on the adhesive. Let **Poly•U** sit for a couple of minutes if adhesive has just come in contact with floor. Let it sit for 15-60 minutes for adhesives that have been in place longer. Once adhesive is softened, wipe up or scrape **Poly•U** and adhesive from the floor. Wipe surface with wet cloth to remove remaining residue.

For Wood Floors on Concrete Surfaces:

Pour or spread **Poly•U** 1/8" thick over highest level of adhesive. Let sit for 8-12 hours. Scrape **Poly•U** and adhesive off concrete. Rinse residue off with water.

CLEAN UP: Use **BLUE BEAR[®] Emerge™ 700DG Degreaser** or soap and water and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess adhesive and **Poly•U** before using a power washer for final cleaning. Allow surface to dry before further preparations.

Coverage: Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

Horizontal: Average coverage is 125 square feet per gallon (maximum 200 square feet per gallon)

Vertical: Average coverage is 75 square feet per gallon

Biodegradable: Meets or exceeds ASTM standards

Precautions: Do not use on site-applied coatings or sealers.

DANGER: Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. May cause reproductive harm. Keep out of reach of children.

⚠ WARNING: This product can expose you to chemicals including n-methyl-2-pyrrolidone, which is known to the state of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Flash Point: Above 200°F (93.3°C)

pH Level: 8.1 pH of 1/10 wt/wt solution in soft water

Ingredients: N-methyl-2-pyrrolidone, dibasic ester LVP, soy ester, ethoxylated alcohol

Volatile Organic Compound (VOC) content: 49.5%, 4.84 lb/g, 578.96 g/l

www.franmar.com
800-538-5069
10282 E 1400 North RD
Bloomington, IL
61705

CHEMICAL EMERGENCY:
Spill, leak, fire, exposure or accident,
call CHEMTREC day or night.
USA and Canada: 800.424.9300
CCN717946 or +1 703.527.3887



www.franmar.com
Rev. 7/16/25