# **Asphalt Remover**

For Modified Asphalts, Polymers, Top Coatings & More



# Remove Asphalt Quickly & Safely!

- No D-Limonene
- Easier Clean-Up Than Traditional Petro Cleaners
- Non Caustic & Eco-Friendly!
- VOC less than 2.3%

# Application & Cleanup

- Spray undiluted ASPHALT REMOVER directly on asphalt build-up. Let sit until build-up has softened.
- Clean Up: Spray clean with pressured hose or power washer



Find Out More About BLUE BEAR Asphalt Remover

Visit: www.franmar.com or Call: 800.538.5069





# **PRODUCT DATA**



# **BLUE BEAR Asphalt Remover**

Taking off difficult, high-oil type asphalts is a snap with **BLUE BEAR ASPHALT REMOVER**. Effectively removes modified asphalts, polymers, top coating, coal tar, and tac-coatings, keeping equipment and tools clean and free of build-up. Not only is **BLUE BEAR ASPHALT REMOVER** a great cleaner, it's a great protectant as well. Pre-applying to metal surfaces before using helps to keep asphalt from bonding tightly to the surface, making cleaning easier than ever!

# **Coverage:**

Average coverage is 100-200 sq ft per gallon.

# **Application:**

Spray undiluted **ASPHALT REMOVER** directly on asphalt build-up. Let sit until build-up has softened. Thicker build-ups may require multiple applications or longer dwell times.

# **Clean Up:**

Spray clean with pressured hose or power washer.

# **Usage Tips from the Pros:**

- Pre-apply ASPHALT REMOVER to clean metal surfaces to help prevent asphalt from bonding.
- For large machinery or application areas, use a pump-up sprayer with chemical resistant seals.
- Build-ups of more than ½" thick may require multiple applications.

### **Biodegradable:**

Meets or exceeds ASTM standards

#### **Precautions:**

**ASPHALT REMOVER** is designed to break down asphalt based surfaces. Protect surfaces not intended for **ASPHALT REMOVER**.

## **Warnings:**

May cause mild skin irritation. May cause eye irritation. May be harmful if swallowed. Keep out of reach of children.

### **Flash Point:**

Above 425°F (218.33°C)

#### pH Level:

6.65 pH of 1/10 wt/wt solution in soft water

### **VOC (Volatile Organic Compounds):**

2.3%, .06 lb/g, 20 g/l California and OTC Compliant

## **Ingredients:**

Soy Ester, Proprietary Surfactant Blend

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

NON-EMERGENCY Call: 800.538.5069 www.franmar.com CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night USA and Canada: **800.242.9300** CCN717946 or **+1 703.527.3887** (Collect Calls Accepted)



PO Box 5565 Bloomington IL 61702

Rev. 3/15/2019