



605PRO

Multipurpose Coatings Remover

With Safenol™

Safer Paint Stripper

- Removes Paints, Urethanes, Enamels, Sealers, Some Epoxies, Lead Paint, and Many Other Coatings
- Gel Formula for Easy Application
- SAFE! No Methylene Chloride, no NMP
- Non-Caustic and Eco-Friendly
- VOC Compliant



Horizontal Coverage: 125 sq ft per gallon
Vertical Coverage: 75 sq ft per gallon

Find Out More About 605PRO Multipurpose Coatings Remover

Visit: www.franmar.com or
Call: 800.538.5069



PRODUCT DATA



605PRO Multipurpose Coatings Remover With Safenol™

- Removes Paints, Urethanes, Enamels, Sealers, Some Epoxies, Lead Paint, + More
- Removes Multiple Layers in ONE Application
- SAFER! No NMP or Methylene Chloride
- Save Money! 605PRO can be reused on the Same Project*
- Non-Caustic and Eco-Friendly

605PRO with Safenol™

605PRO is an effective stripper without using Methylene Chloride or NMP. Using BLUE BEAR's new Safenol™, this stripper effectively removes multiple layers of paint, varnish, enamel, urethane, other simple coatings, and lead based paint. **605PRO** is a safe, low odor, eco-friendly, non-caustic coating remover for your next job.

Usage Tips from the Pros:

- When used outdoors, or for longer dwell times, cover with a 2 mil or thicker plastic sheeting over the work area to help keep stripper wet and working.

Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

Application:

Shake well. Apply a 2-3mm layer of **605PRO** by pouring, brushing, squeegee, or commercial airless sprayer. Applying too thin will cause **605PRO** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

Clean Up:

Use **700DG** and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess coating(s) and **605PRO** before using a power washer for final cleaning. Allow surface to dry before further preparations.

*605PRO can be reused on the same project if stripper retains gel consistency. Spread used 605PRO onto unstripped areas using the application instructions above.

Coverage:

Coverage per square foot varies depending on type and age of coating, number of layers, and method of application. Thickness of the stripper should exceed the thickness of coatings being removed.

Horizontal: Average coverage is 125 sq ft per gallon (max 200 sq ft per gallon)

Vertical: Average coverage is 75 sq ft per gallon

Precautions: Concrete surfaces may darken with use of **605PRO**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

Warnings: May cause eye irritation. Keep out of reach of children.

Flash Point None

pH Level 6.5

VOC (Volatile Organic Compounds) 49%, 4.16lb/g, 497g/L
California and OTC Compliant

Ingredients: Dibasic ester, proprietary thickening, and surfactant blend

Safe for Use On: Concrete, masonry, wood, metal, and fiberglass *Fiberglass must be attended. If left too long, 605PRO could degrade resin.

Do Not Use On: PVC, drywall, limestone, plastic, veneer, terrazzo tile, or rubber

⚠ WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

NON-EMERGENCY
Call: 800.538.5069
www.franmar.com
PO Box 5565
Bloomington IL 61702

CHEMICAL EMERGENCY:
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
USA and Canada: **800.242.9300**
CCN717946 or **+1 703.527.3887**

Rev. 3/17/2019

franmar.com
800.538.5069

