



SafenolTM PRO

605PRO

Multipurpose Coatings Remover

A SAFER PAINT STRIPPER

- Removes paints, urethanes, enamels, sealers, some epoxies, lead-based paint and more
- Gel formula for easy application
- Low-odor formula is ideal for use in occupied areas
- Non-caustic and eco-friendly



*Horizontal Coverage: 125 sq ft per gallon
Vertical Coverage: 75 sq ft per gallon*

See our full line of products

Visit: www.franmar.com or
Call: 800.538.5069





PRODUCT DATA



Safenol™ PRO 605PRO Multipurpose Coatings Remover

BLUE BEAR® Safenol™ PRO 605PRO Multipurpose Coatings Remover effectively removes multiple layers of acrylics, topical sealers, latex, enamels, urethanes, some epoxies and other single-component coatings in one application. With no methylene chloride or other harsh chemicals, **Safenol PRO** is the safer, low-odor, green coatings remover you need to get the job done. Our innovative formula is changing how paint is stripped by doing it effectively without compromising safety for the end user.

Usage Tips:

- For tough coatings or numerous layers, use a notched ½" squeegee or ¼" gauge rake. Square footage will be greatly reduced.
- When used outdoors, cover with a 2 mil or thicker plastic to help keep **Safenol PRO** wet and working.

Coverage: Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

Horizontal: Average coverage is 125 square feet per gallon (maximum 200 square feet per gallon).

Vertical: Average coverage is 75 square feet per gallon.

Test Area: Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

Application: SHAKE WELL. Apply a thick layer of **Safenol PRO** by pouring, brushing, squeegee or commercial airless sprayer. Applying too thin will cause **Safenol PRO** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

Clean Up: Use **BLUE BEAR® Emerge™ 700DG Degreaser** or water and a scrub brush, mop or power washer to clean remaining thin residue. Remove excess coating(s) and **Safenol PRO** before using a power washer for final cleaning. Allow surface to dry before further preparations.

NON-EMERGENCY
Call: 800.538.5069
www.franmar.com
Bloomington, IL
61702

CHEMICAL EMERGENCY:
Spill, leak, fire, exposure or accident,
call CHEMTREC day or night.
USA and Canada: 800.424.9300
CCN717946 or +1 703.527.3887
(Collect calls accepted)

Storage: Keep container closed when not in use.

Precautions: Protect plants and vegetation with a plastic drop cloth. Store above 32°F, **Safenol PRO** will freeze. Wear safety glasses to avoid splatters causing eye irritation, chemical-resistant gloves to protect from skin irritation and dryness, and work-appropriate shoes.

Biodegradable: Meets or exceeds ASTM standards

Flash Point: None

pH Level: 6.5 pH of 1/10 wt/wt solution in soft water

CAUTION: Causes mild skin irritation. Causes eye irritation. May be harmful if swallowed. May be harmful if inhaled. Keep out of reach of children.

Ingredients: Safenol™, dibasic ester, proprietary thickening and surfactant blend

VOC (Volatile Organic Compound) content:
49%, 4.16lb/g, 497g/L

Safe for Use On: Concrete, masonry, wood, metal and fiberglass*
*Fiberglass must be attended. If left too long, **Safenol PRO** could degrade resin.

Do Not Use On: PVC, drywall, limestone, plastic, veneer, terrazzo tile or rubber



www.franmar.com
Rev. 12/21/22